

## Liquid Scintillation Analyzers

# Tri-Carb 2810TR Low Activity Liquid Scintillation Analyzer



Tri-Carb 2810TR

## Description

The Tri-Carb® 2810TR LSA is a computer controlled benchtop liquid scintillation analyzer for detecting small amounts of alpha, beta and gamma radioactivity.

## Standard instrument features

- **Powerful computer system control** on a dedicated ergonomic support arm with 2 GB (minimum) RAM and 80 GB hard disk (minimum), built-in DVD R/W and EtherNet support.
- **Robust downloading sample changer mechanism** with an electrostatic controller and a double light sealing shutter that allows the photomultiplier tube detectors to remain on for maximum stability even during sample changing.
- **Patented TR-LSC® (Time-Resolved Liquid Scintillation Counting)** is featured for high sensitivity, low background counting of LS samples. TR-LSC increases sample throughput and reduces cocktail consumption.
- **Multi-parameter linear MCA (Multichannel Analyzer)** with an effective resolution of 1/10 keV, offers an extended dynamic quench range and provides multi-parameter spectrum analysis to correct for luminescence, color quenching and background radiation.
- **Live SpectraView™ automatic spectrum display** aids in optimizing counting conditions and helps evaluate complex sample situations. It allows setting temporary regions on the spectrum screen and enables the operator to monitor the effect of AEC (Automatic Efficiency Control) while the sample is counting.
- **<sup>133</sup>Ba low energy external standard source and tSIE (transformed Spectral Index of External standard) calculations** eliminate the effects of vial glow, plastic wall and cocktail changes on the DPM results. The use of integral spectrum counts eliminates the need for repeat counting of the external standard and negates the effect of isotope half-life on quench monitoring accuracy and precision. The <sup>133</sup>Ba external standard is centered under the sample vial which eliminates the effects of volume variations and assures reproducible quench monitoring for the life of the instrument.
- **A cassette-loaded bi-directional sample conveyor mechanism** is standard with a sample capacity of either 408 standard 20 mL vials, or 720 small 4 or 7 mL vials depending upon configuration purchased.

- **Positive sample identification** provides protocol number, cassette number, sample number, and user-selectable printout and data file storage of the counting time and date for each sample.
- **Quick-Count sample loading** for 15 independent protocols (with unlimited assays) provides unrestricted access to sample changer and protocol selection plugs. Sample batches are processed by simply activating the Quick-Count protocol plugs, thus minimizing any user programming.
- **Anti-jam recovery** of the sample changer mechanism protects samples, vials and the counting system from damage if obstructions occur.
- **Automatic power-fail recovery** restarts counting when power is restored and the instrument has reinitialized itself.
- **Date and time clock** provides real time display and time-stamped printouts; battery supported.
- **Password protection** prevents unwanted changes to saved assays.
- **Printed header** contains instrument serial number, user ID, and drive and path of all electronic stored data. Each printed page or RTF (Rich Text Format) file report is numbered and dated for GLP compliance.
- **Assay-specific, user selectable, coincidence resolving time** enables optimized counting of any fast or slow, liquid or solid scintillator, for SPAs (Scintillation Proximity Assays), solid scintillation filters and the newer liquid scintillation cocktails.
- **Background subtraction** can be nominated via sample, entered value or stored IPA background spectrum.
- **Programmable single photon counting** enables luminescence assay counting with optimized signal-to-background ratios. It overcomes problems associated with excessive luminescence.

### Standard software features

- **QuantaSmart™ software with comprehensive on-line context sensitive help for the Windows® 7 operating system** is a 32-bit operating system software that provides a robust multitasking, easy networking environment and unlimited assays in a secure multiuser environment.
- **SpectraBase counting and data management system** provides regionless counting and storing of complete spectra for all samples and standards. Features include automatic recall of spectra stored in the quench library for region-independent quench correction and postprocessing of sample data with the optional Replay™ feature.
- **Auto QA (Automatic Quality Assurance)** automatically prints reports for backgrounds, efficiencies, E<sup>2</sup>/B, and Chi-square values for both <sup>3</sup>H and <sup>14</sup>C including the date and time for each test. Auto QA results may be transmitted via RS-232 for archiving.
- **SIS (Spectral Index of Sample) quench indicating parameter** determines counting efficiency by analysis of sample spectrum.
- **Luminescence detection and reporting** with percent luminescence is flagged on printout to alert user of possible sample problems.
- **Enhanced Direct DPM** technique determines the DPM of any single label pure beta or beta/gamma radionuclide in any cocktail without the use of quench standards.
- **Automatic spectrum plot** (on demand) per sample allows spectral documentation of samples.
- **Sample screening** allows screening numeric fields such as activity based on several criteria including background levels, a hard number or within a range of activities or values. Hits can easily be identified in reports with optional highlighting and custom hit flags.
- **Preset time (up to 9,999.99 minutes) and preset error coincidence termination** optimizes counting accuracy in the three counting regions.
- **Percent of standard calculations** is present for single, dual and triple label samples.
- **User adjustable assay-specific sample precount delay** permits dark adaptation of samples before counting.
- **Automatic processing of count data to final results** provides automatic, protocol specific data processing for all user applications, including commercial or user-generated software. No exporting of data to offboard storage devices or computers is required.
- **Spectral unfolding** separates and displays the individual radionuclide spectra of dual label samples in color (requires color-corrected dual label DPM option).
- **3D (three-dimensional) spectral mapping** displays in color the quench standard spectra together with the spectrum of the unknown for single label DPM counting (requires color-corrected dual label DPM option).
- **Half-life correction to any date and time** is available for up to three radionuclides.
- **Decay computations** automatically calculate decay corrected DPM values for commonly used radionuclide standards.
- **Activity reporting** is provided in Becquerels, micro-Curies, or picoCuries
- **Independent output formatting to printer, RS-232 and disk storage** for each protocol provides almost unlimited flexibility in data reporting. Electronic data can be saved to disk in ASCII, RTF, Lotus® or Microsoft® Excel® compatible formats. Reports can be customized for data content and protocol information.

- **Group PrioStat™ interrupt mode** gives priority counting status to a batch of samples counted according to any stored protocol conditions. It automatically restores the interrupted protocol upon completion and stores PrioStat data for immediate viewing. Data is printed at protocol termination.
- **Computer-aided diagnostics** are used to verify all system functions.

### Hardware options

- **Automatic 2D barcode reader** reads 2D barcodes (factory default setup) or properly sized linear bar codes placed on the vial cap. Barcode readings can be used to create the sample worklist (worklist option required) and optionally save to a file or validate an existing worklist. Barcodes are enabled on individual assays giving the user maximum flexibility in barcode usage.
- **Varisette™ sample changer** enables intermixing and counting of both large and small sample vials without special adapters. Option includes both large vial (12-position) and small vial (18-position) cassettes.
- **Printer** (ink jet or laser jet).
- **Temperature-controlled refrigeration** establishes and maintains optimum counting conditions for a wide variety of sample types.

### Software options

- **Sample worklist** enables entry, editing and review of worklists for each assay. Automatic creation of worklists is possible with the 2D barcode option, which allows sample identification with user-specified codes for sample printouts and data files.
- **Dynamic color-corrected single and dual label DPM** is based on tSIE with AEC. It includes DPM based on SIS, constant quench DPM, and full spectrum DPM based on spectrum unfolding. AEC corrects for differential quenching effects in multi-label samples. The low energy spectrum of the external standard ensures accurate tracking of  $^3\text{H}$ ,  $^{14}\text{C}$  and other low energy sample spectra over a very wide quench range. Includes factory stored quench standards for  $^3\text{H}$  and  $^{14}\text{C}$  in classical and ULTIMA Gold™ cocktails with **On-screen editing** of quench correction curves and recording of date last modified.
- **60-user protocol option** upgrades the 2810TR to allow for 60-user programming capability.

- **Enhanced Replay sample post-processing** provides complete recall and post-processing of historical count data to eliminate sample recounting. It enables changes to count conditions and reports as well as execution of user application software for optimization of data analysis.
- **Enhanced IPA™ (Instrument Performance Assessment) database** for monitoring efficiencies, backgrounds, E<sup>2</sup>/B and Chi-square values for  $^3\text{H}$  and  $^{14}\text{C}$  over the life of the instrument. IPA flags impending problems and provides both running mean and fixed baseline charts and associated tables for retrospective quality control and pro-active system maintenance. Baseline acquisition is programmable for increased flexibility. IPA data may also be transmitted to an external computer via RS-232 or saved to disk for archiving instrument performance. The most recent IPA time and date stamped data are available on demand for reporting purposes. Each IPA printout includes instrument model, serial number, software version number and calibration standard information.
- **HSCM (High Sensitivity Count Mode)** increases system sensitivity by implementing additional electronic background reduction via TR-LSC. It includes assay specific, user-selectable delay before burst settings for optimization of TR-LSC.
- **Triple-label DPM** is based on tSIE/AEC for accurate spill correction (requires color-corrected single and dual label DPM option).
- **Chemiluminescence correction with response normalization** corrects for luminescence interference to speed up sample counting. Response normalization of the correction circuits eliminates the effect of component drift on the corrected results.
- **SpectraWorks™ spectrum analysis software** for the Windows® operating system analyzes beta, alpha, and gamma spectra and provides simultaneous display for up to four spectra in stacked or overlaid mode. It features zooming to any part of the spectrum; six regions of interest; display of counts or CPM and linear or log spectra; provides automatic and manual scaling; calculates E<sup>2</sup>/B, MDA, peak resolution; allows adding and subtracting of spectra and multiplication and division by constants.

### Accessories

- **Instrument utility cart:** functionally designed general purpose laboratory cart. Supports any PerkinElmer benchtop system.
- **See the Equipment, Chemicals & Supplies section** in the PerkinElmer catalog.

## Physical data

Dimensions:

Height:	18.5 in.	(47 cm)
Width:	40.5 in.	(103 cm)
Depth:	32 in.	(81 cm)
Depth with refrigeration:	44 in.	(112 cm)

Weight:

477 lb (217 kg) with refrigeration

Shipping weight: approximately 700 lb (318 kg)

Electrical Requirements:

100-240 Vac 50/60 Hz

3-prong grounded plug

Power Consumption:

<200 VA; <800 VA with temperature control option

Environmental:

Operating ambient temperature 15 to 35 °C (59 to 90 °F)

Operating relative humidity 30% to 85%

## Typical performance data

(As measured in factory at Downers Grove, Illinois)

Energy Range: 0–2,000 keV

Efficiency, Normal Count Mode:

		Minimum Acceptable
<sup>3</sup> H	0–18.6 keV	60%
<sup>14</sup> C	0–156 keV	95%

Figure of Merit (E<sup>2</sup>/B), Normal Count Mode (NCM):

<sup>3</sup> H	1–18.6 keV	180
<sup>14</sup> C	4–156 keV	380

Figure of Merit (E<sup>2</sup>/B), Low Activity/High Sensitivity Count Mode (HSCM):

<sup>3</sup> H	1–12.5 keV	300
<sup>14</sup> C	14.5–97.5 keV	950

Observed Background, NCM:

		Average
<sup>3</sup> H	0–18.6 keV	17.3 CPM
<sup>14</sup> C	0–156 keV	24.3 CPM

Note: The efficiencies, backgrounds, and E<sup>2</sup>/B values for the Normal Count Mode were determined using PerkinElmer sealed large vial glass standards set P.N. 6008500 verified with NIST standard activity. The HSCM values are determined using PerkinElmer low level sealed large glass vial standards set P.N. 6008914 verified with NIST standard activity. No maximum is specified for background.

### Safety, Radiated Emissions and Immunity:

The Tri-Carb 2810TR has been tested and approved for safety, radiated emissions and immunity according to the standards of CSA, TUV, IEC1010 and CE93.

In the U.S.A. the CSA approval satisfies the requirements of 29CFR 1910.399.

PerkinElmer, Inc.  
940 Winter Street  
Waltham, MA 02451 USA  
P: (800) 762-4000 or  
(+1) 203-925-4602  
[www.perkinelmer.com](http://www.perkinelmer.com)



For a complete listing of our global offices, visit [www.perkinelmer.com/ContactUs](http://www.perkinelmer.com/ContactUs)

Copyright © 2009-2014, PerkinElmer, Inc. All rights reserved. PerkinElmer® is a registered trademark of PerkinElmer, Inc. All other trademarks are the property of their respective owners.

007089D\_01